bimos

characteristics Labster stool

Article: 9107 integral foam

Dimensions in mm

	Seat:	H:	450-650
		B:	380
		T:	380
Packing data	Weight Volume	kg m³	6,0 0,04



Base equipment		Benefit
Hygienic quality	Consistent hygienic design. Quasi seamless, no nooks and crannies, soft cover on ring release.	Completely washable and resistant to disinfectant. Cleaning / decontamination is quick, easy, thorough and safe.
aboratory qualification	GMP-compatible and suitable for use in clean rooms. Can be used in laboratories of safety class S1 to S3	Suitable for laboratory and hygiene-critical areas of all types and in particular for use in the health sector, biotechnology and pharmaceuticals
Seat design	Extra large seat with a diameter of 380 mm	The extra-strong comfort upholstery offers excellent seating comfort.
Seat design	Integral foam cushion (PU) with seamless upholstery technique . Washable and resistant to disinfectant Available in the colors: Black (2000)	The integral foam cushions offer good seating comfort and are resistant to mechanical loads.
Seat height	Grey (2002) Infinitely variable seat height adjustment from 450-650 mm through self-supporting safety pneumatic spring	Large seat height adjustment range.
Fechnology	Ring release	The height can be adjusted at any handle position around the stool.
Castors/Glides	Compact, round flat base.	Can be stowed away under desks to save space. The round base prevents it getting caught anywhere.
Materials used	All materials are pure and recyclable.	Environmentally friendly
Standards	GMP - compatible Laboratory safety class S1 to S3 GS symbol for "Tested safety" Quality management system DIN EN ISO 9001 EEC Directive No. 1836/93 and Environmental management system DIN EN	Certified laboratory suitability Safeguarded procurement

bimos

characteristics Labster stool

Article: 9107 integral foam

Dimensions in mm

	Seat:	H:	450-650
		B:	380
		Т:	380
Packing data	Weight Volume	kg m³	6,0 0,04



Warranty

10 year long-term warranty of which 3 year full warranty

Guaranteed quality and high efficiency