bimos

characteristics Unitec 3 with glides and footring

Article: 9651 integral foam

Dimensions in mm			
	Seat:	H:	580-850
Packing data	Weight	kg	14,0
	Volume	m³	0,15



Base equipment		Benefit
Backrest	Large, ergonomically designed backrest to take the strain off the spine and muscles with integrated lumbar support	Healthy posture due to a hump providing support for the back in the lumbar region
Seat	Backrest height adjustment convenient and easy to handle in sitting position Ergonomically designed seat with rounded front edge	The support area can be adapted in accordance to the user's body size The round front edge of the seat prevents blocked circulation in the thighs
Seat and backrest design	Integral foam (PU): The new developed SoftTouch integral foam provides the ultimate softness in seating, is washable and resistant to external influences Colour: Black (2000)	The use of integral foam is recommended for work environments where the chair is in contact with aggressive substances and sharp parts
Seat height	Stepless seat height setting from 580-850 mm supported by safety gas spring with protective cover	Seat height can be adapted to nearly 95% of all body sizes, the cover protects the gas spring from dust and dirt
Technology	Permanent contact-backrest	This mechanism ensures that the backrest responds immediately to any movements of the upper body by following them. Thus, the back remains supported all the time. The backrest can also be locked into any tilt position if required
	Quick adjustment	Every function can be operated comfortable and easy in sitting position
Base	Black 5 star base made from plastic. Flat design	Very high stability, longevity and safety Flat design prevents stumbling hazard
Glides	Wearproof plastic glides with a large surface Area	Offer a superb level of stability
Foot ring	Chrome-plated foot ring, adjustable in height	Provides support through the wide tread area and can be easily and quickly adjusted in height
Materials	The materials used are recyclable	Environmentally friendly.
Standards	DIN 68 877 German GS "safety tested" mark of confirmity Quality Management System DIN EN ISO 9001	Procuring is insured
Warranty	Regulation EWG Nr. 1836/93 and Environmental Management System DIN ISO 14001 10 year long term warranty, 3 years full warranty	Guaranteed quality and high efficiency

bimos

characteristics Unitec 3 with glides and footring

Article: 9651 integral foam

Dimensions in mm

	Seat:	H:	580-850
Packing data	Weight Volume	kg m³	14,0 0,15



bimos

characteristics Unitec 3 with glides and footring

Article: 9651 integral foam

Dimensions in mm			
	Seat:	H:	580-850
Decking data	W/oight	ka	14,0
Packing data	Weight	kg	0,15
	Volume	m³	0,15



Options

Armrests

Multifunctional armrest

Loop armrest

Benefit

Made of polyamide, adjustable in width (20 mm) The armrests are adjustable in height, width and depth to suit the individual user